



Specification for Approval

- DEVICE NUMBER: BIR-BM17E4G-1

**SAMPLES
ATTACHED AREA**

| DATE \ PAGE | 1 | 2 | 3 | 4 | 5 | CONTENTS | | | | | |
|-------------|-----|-----|-----|-----|-----|------------------|--|--|--|--|--|
| 2015/9/14 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | Initial Released | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

FOR CUSTOMER'S APPROVAL STAMP OR SIGNATURE

| APPROVED | PURCHASE | MANUFACTURE | QUALITY | ENGINEERING |
|----------|----------|-------------|---------|-------------|
| | | | | |

佰鴻工業股份有限公司
 BRIGHT LED ELECTRONICS CORP.
 新北市板橋區和平路 19 號 3 樓
 3F., No.19, He Ping Road,
 Ban Qiao Dist., New Taipei City,
 Taiwan
 Tel: +886-2-29591090
 Fax: +886-2-29547006/29558809
www.brtled.com

| ISSUED | APPROVED | PREPARED |
|---|---|---|
|  |  |  |

END-LOOK PACKAGE LIGHT EMITTING DIODE

● **Features:**

1. High radiant power and high radiant intensity.
2. Standard T-1 3/4(5mm)package.
3. Peak wavelength $\lambda_p=940\text{nm}$.
4. Good spectral matching to si-photodetector.
5. Radiant angle: 30°
6. Lens Appearance: Blue Transparent.
7. This product doesn't contain restriction substance, comply RoHS standard

● **Applications:**


1. Remote Control.
2. Automatic Control System.

● **Absolute Maximum Ratings(Ta=25°C)**

| Parameter | Symbol | Rating | Unit |
|------------------------------------|-----------------|------------|------|
| Power Dissipation | Pd | 150 | mW |
| Continuous Forward Current | I _F | 100 | mA |
| Peak Forward Current ^{*1} | I _{FP} | 1.0 | A |
| Reverse Voltage | V _R | 5 | V |
| Operating Temperature | Topr | -40°C~85°C | - |
| Storage Temperature | Tstg | -45°C~85°C | - |

^{*1} (300pps 10us pulse)

● **Package Dimensions:**









NOTES:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (0.01") unless otherwise specified.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.


● **Optical- Electrical Characteristics (@ $T_A=25^{\circ}\text{C}$)**

| Parameter | Symbol | Test Conditions | Min | TYP | Max | Unit |
|---------------------------|------------------|-------------------|-------|------|-----|---------------|
| Radiant Intensity | I_e | $I_F=50\text{mA}$ | 19.42 | 40 | - | mW/sr |
| Forward Voltage | V_F | $I_F=50\text{mA}$ | - | 1.25 | 1.5 | V |
| Reverse Current | I_R | $V_R=5\text{V}$ | - | - | 100 | μA |
| Peak Wavelength | λ_p | $I_F=50\text{mA}$ | - | 940 | - | nm |
| Spectral Line Half- Width | $\Delta \lambda$ | $I_F=50\text{mA}$ | - | 50 | - | nm |
| Viewing Angle | $2\theta_{1/2}$ | $I_F=20\text{mA}$ | - | 30 | - | deg |

● **Typical Optical-Electrical Characteristic Curves**



● Dip Soldering




1. Please avoid any external stress applied to the lead-frames and epoxy while the LEDs are at high temperature, especially during soldering
2. DIP soldering and hand soldering should not be done more than one time.
3. After soldering, avoid the epoxy lens from mechanical shock or vibration until the LEDs are back to room temperature.
4. Avoid rapid cooling during temperature ramp-down process
5. Although the soldering condition is recommended above, soldering at the lowest possible temperature is feasible for the LEDs


● IRON Soldering

300°C Within 3 sec., One time only.

● Tapping and packaging specifications(Units: mm)



● Packaging Bag Dimensions



Notes:

- 1、500pcs per bag, 5Kpcs per box.
- 2、All dimensions are in millimeters(inches).
- 3、Specifications are subject to change without notice.



Infrared Emitting Diode Specification

- Commodity: Infrared emitting diode
- Intensity Bin Limits (At 50mA)

| BIN CODE | Min.(mW/sr) | Max.(mW/sr) |
|----------|-------------|--------------|
| 13 | 19.42 | 27.20 |
| 14 | 27.20 | 38.08 |
| 15 | 38.08 | 53.31 |
| 16 | 53.31 | 74.63 |
| 17 | 74.63 | 104.48 |

NOTES:Tolerance of measurement of Radiant Intensity :±15%